

23mt RECTANGULAR TABLE PRODUCT SPECS

Revised: September 11, 2012

Models include:

- ▶ 23M06293010MT
- ▶ 23M06273010MT

MATERIALS

a. Tabletop

The core is 3/4" M-3 industrial grade particleboard with average density of 45 P.C.F. The particleboard panel has a smooth surface for laminating. The longer core particles enhance the core strength and dimensional stability.

Tabletop thickness is .80" +/- .020".

A .028 WilsonArt® phenolic backer is bonded to the bottom of the core, providing the fabricated piece with balance and protection from the effects of humidity in their normal use.

The top is laminated with WilsonArt® .030 high-pressure laminate for superior abrasion resistance. Meets or exceeds NEMA specifications. Top is secured to frame with #10 x 3/4" screws for superior holding power and ease of replacement, 9" on centers.

Edges are sealed and finished with black EdgeGuard™. EdgeGuard™ is a sprayed on polyurea edge treatment that provides superior resistance to moisture, eliminates unsanitary food traps, and is extremely tamper resistant. Additional colors are available: desert sand, slate, tan, country blue, light gray, and red brick.

b. Frame

Self-supporting unitized frame design uses dual 14-gauge 1" vertical steel tubing, 14-gauge 1" steel tubing for leg pivot tubes, and 14-gauge 1" x 2" rectangular leg base steel tubing. Tabletops are spanned with 16-gauge aprons with a full 180-degree hem for the effective strength of 11-gauge steel. Table frame is structured to give maximum strength and rigidity.

All metal parts of the frame are thoroughly cleaned to resist corrosion and provide maximum paint adhesion. Metal is finished with high-grade electrostatically applied, baked-on epoxy powder to resist abrasion, marring and scratching. Chrome plating optional at an additional charge.

c. Table Undercarriage

Self-supporting unitized frame design. Latching is automatic in both storage and use positions.

Table rolls on four 4" diameter x 1-1/4" wide Poly II gray rubber, ball-bearing swivel casters. Poly II rubber wheels provide excellent floor protection, abrasion resistance, good impact strength, quiet operation, and rolling ease. They are non-marking, and resistant to water, oil and most acids and chemicals.

23mt RECTANGULAR TABLE PRODUCT SPECS

STORAGE FOOTPRINT

Two tables in the stored position should occupy an area of 30" wide or 36" wide x 80" long. Each additional table adds 40" to the stacked length.

CERTIFICATIONS AND PERFORMANCE STANDARDS

GREENGUARD® Certification We have been awarded both the GREENGUARD Indoor Air Quality Certification® and the more stringent Children & Schools Certification (daycare and K-12) by the GREENGUARD Environmental Institute (GEI). All GREENGUARD® products have been tested for their chemical emissions performance and can be found in the GREENGUARD® product guide at greenguard.org.

UL Listed Tested by Underwriters Laboratories; meets the more stringent safety standards contained in UL Standard for Safety for Folding Rollaway Tables, UL 2040.

(*) Not UL Listed at this time. UL Pending.

WARRANTY

As part of Palmer Hamilton's ongoing commitment to quality, product specification changes or modifications may be made without prior notice.

Palmer Hamilton warrants that its products shall be free from defects in original material and workmanship for a period of fifteen years from the original shipment date. This warranty shall not apply to normal wear and tear or in the event products are damaged as a result of misuse, abuse, vandalism, neglect, accident, improper application, and modification or repair by persons not authorized by Palmer Hamilton.

The company will, at its discretion, repair or replace any defects. Any repair or replacement must be approved in advance by the factory before any action is taken. There are no implied warranties of fitness or merchantability, and there are no other express warranties beyond the warranties expressed here.



1-800-788-1028

For a complete listing of all our products
visit our website at palmerhamilton.com



made in the
USA

