

RE+LOAD"



Specs for DC & SC Models Features, Construction and Accessories

- RE-LOAD Power options untethered (DC), untethered self-charge (SC)
- DC Untethered does not have charger provided, must use with battery cart.
- SC Untethered supplies charger in battery compartment.
- Table thickness 1 1/8" M3 particle board w/.030" vertical grade laminate with balanced backer.
- Edge Options/Materials SmartEdge, durable casted polyurethane edge.
- Laminate Options Wilson Art -60 or -38, other options available at up-charge.
- Table base is made from sturdy tubular steel design.
- Casters 2 ½" twin caster w/locking brake in black only.
- Glides 1 1/2" diameter adjustable non swivel glide in black only. Adjustable to 5/8" vertical.
- Backpack hooks standard on 42" high unit only.
- Battery Compartment locking keyed access, keyed alike, 2 keys included.
- Power availability (charging time) will depend on devices, amount of consistent charging time and temperature of environment. Approximately 5 hrs if charging 4 Apple tablets or 8+ hrs for phones and other devices. Battery will re-charge in 4 5 hours after connecting to charger and plugging into wall.
- Battery 12V 18Ah sealed lead acid battery (SLA), maintenance free. Keep from freezing temperatures for long periods of time or extreme heat for DC. This will assist the system in being trouble free.
- DC Power 12 V system providing 2 amp draw from each port. When battery hits 10%, light turns from BLUE LED to RED LED and will require charging of the battery, hub will continue to charge until RED LED turns off. Even though battery will not charge after this point, it will still hold a charge. There is a designed safety shutoff on the battery so it will not go into a deep discharge mode, hence, increasing the life of the battery. Deep discharging of a battery will significantly reduce the life of the battery. Under normal conditions and charging, the battery life should last around 3+ years.





Reload DC SC Spec Sheet 08062019





- The charger supplied, either in the charging cart or self-charge, is a 5-stage charger which will maximize the life of the battery also.
- Do not plug charger to charging hub, nothing will happen. It will not provide power to charging hub.
- There is a 7.5A blade fuse in the system to provide a safeguard from damaging the system.
- Warranty 1 year on charging hub, charger, and battery and 5 years remaining components (top and base).
- Recharging Cart 120V plug into wall outlet, 20amp circuit required 8 chargers, 8 batteries, included with charging cart. Recharging cart sold separately from table. Measures 39 1/2" H x 39 ½" W x 20 1/2 "D.
- Separate components, batteries and chargers, will be available for individual purchase, but only come with a 30-day warranty period.
- All RE-LOAD's and batteries MUST ship ground transportation.







RE-LOAD Product Dimensions and Weights

Please note, add 2" for height to include the charging hub.

29" High Untethered with Casters Include One Battery	Squircle – DC	Weight	29" High Untethered With Glides Includes One Battery	Squircle - DC	Weight
•	29x30x30	57	,	29x30x30	57
	29x36x36	67		29x36x36	67
	29x42x42	78		29x42x42	78
	Round - DC			Round - DC	
	29x30	55		29x30	55
	29x36	65		29x36	65
	29x42	76		29x42	76
42" High Untethered With Casters Includes One Battery	Squircle - DC		42" High Untethered With Glides Includes One Battery	Squircle - DC	
	42x30x30	71		42x30x30	71
	42x36x36	82		42x36x36	82
	Round - DC			Round - DC	
	42x24	58		42x24	58
	42x30	69		42x30	69
	42x36	80		42x36	80
29" High Self- Charge With Casters Includes One Battery and One Battery Charger	Squircle - SC		29" High Self- Charge With Glide Includes One Battery and One Battery Charger	Squircle - SC	
	29x30x30	58		42x30x30	58
	29x36x36	68		42x36x36	68
	29x42x42	79			79
	Round - SC			Round - SC	
	29x30	56		42x30	56
	29x36	66		42x36	66
	29x42	77			77



42" High Self- Charge With Casters Includes One Battery and One Battery Charger	Squircle - SC		42" High Self- Charge With Glide Includes One Battery and One Battery Charger	Squircle - SC	
-	42x30x30	72		42x30x30	72
	42x36x36	83		42x36x36	83
	Round - SC			Round - SC	
	42x30	70		42x30	70
	42x36	81		42x36	81



RE-LOAD Shipping Dimensions and Weights – Ships assembled in box on pallet. Freight class 250.

29" High Untethered with Casters Include One Battery	Squircle – DC	Weight	29" High Untethered With Glides Includes One Battery	Squircle - DC	Weight
33x33x39	29x30x30	116	33x33x39	29x30x30	116
45x45x39	29x36x36	138	45x45x39	29x36x36	138
45x45x39	29x42x42	149	45x45x39	29x42x42	149
	Round - DC			Round - DC	
33x33x39	29x30	115	33x33x39	29x30	115
45x45x39	29x36	136	45x45x39	29x36	136
45x45x39	29x42	147	45x45x39	29x42	147
42" High Untethered With Casters Includes One Battery	Squircle - DC		42" High Untethered With Glides Includes One Battery	Squircle - DC	
33x33x52	42x30x30	130	33x33x52	42x30x30	130
45x45x52	42x36x36	153	45x45x52	42x36x36	153
	Round - DC			Round - DC	
33x33x52	42x30	128	33x33x52	42x30	128
45x45x52	42x36	151	45x45x52	42x36	151
29" High Self- Charge With Casters Includes One Battery and One Battery Charger	Squircle - SC		29" High Self- Charge With Glide Includes One Battery and One Battery Charger	Squircle - SC	
33x33x39	29x30x30	117	33x33x39	42x30x30	117
45x45x39	29x36x36	139	45x45x39	42x36x36	139
45x45x39	29x42x42	150	45x45x39		150
	Round - SC			Round - SC	
33x33x39	29x30	116	33x33x39	42x30	116
45x45x39	29x36	137	45x45x39	42x36	137
45x45x39	29x42	148	45x45x39		148



42" High Self- Charge With Casters Includes One Battery and One Battery Charger	Squircle - SC		42" High Self- Charge With Glides Includes One Battery and One Battery Charger	Squircle - SC	
33x33x52	42x30x30	131	33x33x52	42x30x30	131
45x45x52	42x36x36	154	45x45x52	42x36x36	154
	Round - SC			Round - SC	
33x33x52	42x30	129	33x33x52	42x30	129
45x45x52	42x36	152	45x45x52	42x36	152